

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Product name** : H.B. Fuller® Tempo Sohlenlöser**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-  
stance/Mixture : AdhesiveRecommended restrictions  
on use : For industrial use only.**1.3 Details of the supplier of the safety data sheet**

Company : H.B. Fuller, Isar-Rakoll, S.A.

Address : Estrada Nacional 13  
PT-4486-851 Mindelo - Vila do Conde  
+351 229 288 200E-mail address of person  
responsible for the SDS : EU-MSDS@hbfuller.com**1.4 Emergency telephone number**

Emergency telephone number : +44 1235 239 670 (24 hours)

National Poisons Information Centre (NPIC): 01 809 2566 (24  
hours)**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe mist or vapours.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

##### **Response:**

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

##### **Hazardous components which must be listed on the label:**

toluene  
Reaction mass of ethylbenzene and m-xylene and p-xylene

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
toluene	108-88-3 203-625-9 601-021-00-3 01-2119471310-51-0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 70 - < 90
Reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 905-562-9 01-2119555267-33-0000	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT RE 2; H373 Acute Tox. 4; H312, H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 10 - < 20

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : If on clothes, remove clothes.  
Move the victim to fresh air.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

- |                         |   |   |
|-------------------------|---|---|
| If inhaled              | : | Remove person to fresh air. If signs/symptoms continue, get medical attention.<br>In case of unconsciousness bring patient into stable side position for transport.                                   |
| In case of skin contact | : | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.<br>If skin irritation persists, call a physician.   |
| In case of eye contact  | : | Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.  |
| If swallowed            | : | If accidentally swallowed obtain immediate medical attention.<br>Rinse mouth with water.<br>If conscious, drink plenty of water.<br>Do NOT induce vomiting.<br>If symptoms persist, call a physician. |

**4.2 Most important symptoms and effects, both acute and delayed**

None known.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment : No further relevant information available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- |                                |   |  |
|--------------------------------|---|--|
| Suitable extinguishing media   | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Water mist<br>Foam<br>Dry powder<br>Carbon dioxide (CO <sub>2</sub> ) |
| Unsuitable extinguishing media | : | Water with a full water jet  |

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during fire-fighting : No further relevant information available.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : No special protective measures against fire required.

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

Further information : In the event of fire, wear self-contained breathing apparatus. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

---

#### SECTION 6: Accidental release measures

##### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Use breathing protection against the effects of fumes/dust/aerosol.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.

##### 6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.  
Prevent the material from reaching sewage system, holes and cellars.  
If the product contaminates rivers and lakes or drains inform respective authorities.

##### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable containers.  
Dispose of contaminated material as waste according to section 13.

##### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

---

#### SECTION 7: Handling and storage

##### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of dust and aerosols.  
Use only with adequate ventilation.  
Take note of emission threshold.  
Use solvent-proof equipment.  
Ensure that suitable extractors are available on processing

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

machines.  
Handle with care.  
Keep eye wash bottle available on working place.  
Avoid release to the environment.  
Keep away from children.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep dark, cool and dry. Store in cool place.

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

#### 7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
toluene	108-88-3	TWA	50 ppm 192 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 384 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		OELV - 8 hrs (TWA)	50 ppm 192 mg/m <sup>3</sup>	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	100 ppm 384 mg/m <sup>3</sup>	IE OEL

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version 1.0      Revision Date: 03.04.2022      SDS Number: 100000017519      Date of last issue: -  
Date of first issue: 03.04.2022

Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
toluene	Workers	Dermal	Long-term systemic effects	384 mg/kg
	Workers	Inhalation	Acute systemic effects	384 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	384 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	192 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	192 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene	Workers	Inhalation	Acute systemic effects	289 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	180 mg/kg
	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
toluene	Fresh water sediment	0,68 mg/l
	Marine sediment	0,68 mg/l
	Sewage treatment plant	13,61 mg/l
	Fresh water sediment	16,39 mg/kg
	Marine sediment	16,39 mg/kg
	Soil	2,89 mg/kg
Reaction mass of ethylbenzene and m-xylene and p-xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg

## 8.2 Exposure controls

### Engineering measures

Please take care on national and local requirements.

### Personal protective equipment

Eye protection : Tightly fitting safety goggles

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

Hand protection

Remarks : The glove material has to be impermeable and resistant to the product/the substance/the preparation.  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
The gloves need to be disposed after the penetration time and replaced by new ones.  
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

**For the permanent contact gloves made of the following materials are suitable:**

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

**As protection from splashes gloves made of the following materials are suitable:**

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection : Protective clothing

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus.  
In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.  
Ensure that suitable extractors are available on processing

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

machines.

Protective measures : Keep away from food, drink and animal feedingstuffs.  
Instantly remove any soiled and impregnated garments.  
Wash hands before breaks and immediately after handling the product.  
Avoid contact with the eyes and skin.  
Store protective clothing separately.

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Physical state	: liquid
Colour	: colourless
Odour	: solvent-like
Odour Threshold	: is not determined
Melting point/freezing point	: is not determined
Boiling point/boiling range	: 111 °C
Flash point	: 4 °C
Auto-ignition temperature	: is not determined
Decomposition temperature	: not applicable
pH	: is not determined
Solubility(ies)	
Water solubility	: not miscible or difficult to mix
Partition coefficient: n-octanol/water	: no data available
Vapour pressure	: 29 hPa (20 °C)
Density	: 0,87 g/cm <sup>3</sup>
Relative vapour density	: is not determined

**9.2 Other information**

Explosives	: Product is not explosive. However, formation of explosive
------------	---

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

vapour/air mixtures is possible.

Evaporation rate : is not determined

---

#### SECTION 10: Stability and reactivity

##### 10.1 Reactivity

No further relevant information available.

##### 10.2 Chemical stability

No decomposition if used according to the specifications.

##### 10.3 Possibility of hazardous reactions

Hazardous reactions : Develops readily flammable vapours/fumes.

##### 10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

##### 10.5 Incompatible materials

Materials to avoid : No further relevant information available.

##### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

#### SECTION 11: Toxicological information

##### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

###### Acute toxicity

###### Product:

Acute oral toxicity : Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Based on available data, the classification criteria are not met.

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: Calculation method

Acute dermal toxicity : Based on available data, the classification criteria are not met.

###### Components:

toluene:

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

Acute oral toxicity : LD50 Oral (Rat): 5.580 mg/kg

Acute inhalation toxicity : LC50 (Rat): 12,5 mg/l  
Exposure time: 4 h**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

**SECTION 12: Ecological information****12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil****Product:**Mobility : Medium: Soil  
Remarks: Do not allow product to reach ground water, water bodies or sewage system., Very toxic to aquatic organisms, Toxic effects on fish and plankton, Danger to drinking water if even extremely small quantities leak into soil.**12.5 Results of PBT and vPvB assessment****Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Endocrine disrupting properties****Product:**

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

No data available

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not dispose of waste into sewer.  
Hand over to disposers of hazardous waste.  
The generation of waste should be avoided or minimized wherever possible.  
Incinerate under controlled conditions in accordance with all local and national laws and regulations.  
Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (\*).

#### Waste accruing during application:

08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances  
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

#### Waste accruing during cleaning:

08 04 11\* adhesive and sealant sludges containing organic solvents or other dangerous substances  
08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

#### Waste packaging:

15 01 01 paper and cardboard packaging  
15 01 02 plastic packaging  
15 01 04 metallic packaging  
15 01 10\* packaging containing residues of or contaminated by dangerous substances.

Contaminated packaging : Disposal must be made according to official regulations.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

**SECTION 14: Transport information****14.1 UN number or ID number**

<b>ADR</b>	:	UN 3295
<b>RID</b>	:	UN 3295
<b>IMDG</b>	:	UN 3295
<b>IATA</b>	:	UN 3295

**14.2 UN proper shipping name**

<b>ADR</b>	:	HYDROCARBONS, LIQUID, N.O.S.
<b>RID</b>	:	HYDROCARBONS, LIQUID, N.O.S.
<b>IMDG</b>	:	HYDROCARBONS, LIQUID, N.O.S.
<b>IATA</b>	:	HYDROCARBONS, LIQUID, N.O.S.

**14.3 Transport hazard class(es)**

<b>ADR</b>	:	3
<b>RID</b>	:	3
<b>IMDG</b>	:	3
<b>IATA (Cargo)</b>	:	3

**14.4 Packing group**

<b>ADR</b>	:	UN3295
<b>RID</b>	:	UN3295
<b>IMDG</b>	:	
Packing group	:	II
Labels	:	3
EmS Code	:	F-E, S-D
<b>IATA (Cargo)</b>	:	UN3295
<b>IATA_P (Passenger)</b>	:	UN3295

**14.5 Environmental hazards**

<b>ADR</b>	:	
Environmentally hazardous	:	no

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable for product as supplied.

---

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : not applicable

RoHS: 2011/65/EU, Restriction of Hazardous Substances : not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : not applicable

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

---

emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 100,00 %, 870,0 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) not applicable

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### The components of this product are reported in the following inventories:

TSCA	:	All substances listed as active on the TSCA inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
REACH	:	On the inventory, or in compliance with the inventory

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

---

### SECTION 16: Other information

#### Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.

## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

### H.B. Fuller® Tempo Sohlenlöser

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361d	:	Suspected of damaging the unborn child.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H412	:	Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2006/15/EC	:	Europe. Indicative occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**H.B. Fuller® Tempo Sohlenlöser**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2022	100000017519	Date of first issue: 03.04.2022

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department  
EU-MSDS@hbfuller.com

**Classification of the mixture:**

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Repr. 2	H361d
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

**Classification procedure:**

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN