

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

140 Vulkofest 96 toluene-free contact adhesive
UFI: WXTW-20DC-N006-8CSH

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

1.3 Details of the supplier of the safety data sheet

Supplier

Renia Gesellschaft mbH
Ostmerheimer Straße 516 Telephone: +492216307990
51109 Köln E-mail: info@renia.com
Deutschland Website: www.renia.com

Department responsible for information

E-mail (competent person) labor@renia.com

1.4 Emergency telephone number

24 hr. emergency phone number: +49-221-630799-17

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
Flam. Liq. 2; flammable liquids; H225 Highly flammable liquid and vapour.
Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation.
STOT SE 3 Narcotic effects; STOT-single exposure; H336 May cause drowsiness or dizziness.
Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.
Aquatic Chronic 2; Hazardous to the aquatic environment; H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS02 GHS07 GHS09

Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H315 Causes skin irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P391 Collect spillage.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

ethyl acetate

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

* **Supplemental hazard information**

EUH208 Contains bis-[4-(2,3-epoxipropoxy)phenyl]propane, rosin; colophony. May produce an allergic reaction.

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

polychloroprene adhesive with modified synthetic resins and stabilizers in a mixture of organic solvents.

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
* 141-78-6 205-500-4 607-022-00-5	ethyl acetate 01-2119475103-46 Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066 ATE (oral): > 5.620 mg/kg ATE (dermal): > 18.000 mg/kg ATE (inhalative): = 56 mg/L (4 h)	25,0 < 35,0
* 110-82-7 203-806-2 601-017-00-1	cyclohexane 01-2119463273-41-0000 Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / Skin Irrit. 2 H315 / STOT SE 3 H336 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410 ATE> 5.000 mg/kg ATE (inhalative): > 32,88 mg/L (4 h) ATE (dermal): > 2.000 mg/kg	20,0 < 25,0
* - 921-024-6 649-328-00-1	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 01-2119475514-35 Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / Skin Irrit. 2 H315 / STOT SE 3 H336 / Aquatic Chronic 2 H411 / EUH066 ATE> 5.000 mg/kg ATE> 20 mg/L (4 h) ATE (dermal): > 2.000 mg/kg	20,0 < 25,0
* 8050-09-7 232-475-7 650-015-00-7	rosin; colophony 01-2119480418-32 Skin Sens. 1 H317 ATE> 2.000 mg/kg bw ATE (dermal): > 2.000 mg/kg bw	0,1 < 1,0
* 1675-54-3 216-823-5 603-073-00-2	bis-[4-(2,3-epoxipropoxy)phenyl]propane Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Aquatic Chronic 2 H411 Specific concentration limit (SCL) Eye Irrit. 2 H319: >= 5,00 / Skin Irrit. 2 H315: >= 5,00	0,1 < 1,0
* 128-37-0 204-881-4 -	2,6-di-tert-butyl-p-cresol 01-2119555270-46 Aquatic Acute 1 H400 / Aquatic Chronic 1 H410 ATE (oral): > 5.000 mg/kg ATE (dermal): > 5.000 mg/kg	0,1 < 1,0

Remark

Full text of H- and EUH-statements: see section 16. Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove affected person from the danger area and lay down.

Following inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

Following skin contact

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Transport affected person in lying position, in case of shortness of breath in half-sitting position. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), alcohol resistant foam, Extinguishing powder, ABC-powder, spray mist, (water), Dry sand.

Unsuitable extinguishing media

Full water jet. Strong water jet.

5.2 Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Hazardous combustion products.

5.4 Additional information

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes and skin. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Before starting work, apply solvent-resistant skincare preparations.

Further information

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours/aerosols must be exhausted directly at the point of origin. Take precautionary measures against static discharge.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Store in a well-ventilated and dry room at temperatures between 10 °C and 30 °C. Ensure adequate ventilation of the storage area.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Hints on joint storage

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances. Store packaging and ignitable materials separately. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean. Store small packages in a suitable, robust cabinet.

7.3 Specific end use(s)

Adhesives, sealants, Roller application or brushing of adhesive and other coating.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
128-37-0	2,6-di-tert-butyl-p-cresol	WEL	10 / - (-) mg/m ³
110-82-7	cyclohexane	WEL	350 / 1.050 (-) mg/m ³
141-78-6	ethyl acetate	WEL	734 / 1.468 (-) mg/m ³
-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	WEL	1.800 / - (-) mg/m ³
8050-09-7	rosin; colophony	WEL	0,05 / 0,15 (-) mg/m ³

Additional information

Long-term: Long-term occupational exposure limit value
short-term: short-term occupational exposure limit value

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
128-37-0	2,6-di-tert-butyl-p-cresol	DNEL long-term inhalative (systemic)	5,8 mg/m ³
128-37-0	2,6-di-tert-butyl-p-cresol	DNEL long-term dermal (systemic)	8,3 mg/kg bw/day
110-82-7	cyclohexane	DNEL long-term dermal (systemic)	2.016 mg/kg
110-82-7	cyclohexane	DNEL long-term inhalative (systemic)	0,7 mg/L
141-78-6	ethyl acetate	DNEL long-term inhalative (systemic)	1,468 mg/L
141-78-6	ethyl acetate	DNEL acute inhalative (local)	1,468 mg/L
141-78-6	ethyl acetate	DNEL long-term dermal (systemic)	63 mg/kg
-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term dermal (systemic)	773 mg/kg
-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term inhalative (systemic)	2.035 mg/m ³
8050-09-7	rosin; colophony	DNEL long-term inhalative (systemic)	117 mg/m ³
8050-09-7	rosin; colophony	DNEL long-term dermal (systemic)	17 mg/kg bw/day

DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
128-37-0	2,6-di-tert-butyl-p-cresol	DNEL long-term inhalative (systemic)	1,74 mg/m ³
128-37-0	2,6-di-tert-butyl-p-cresol	DNEL long-term dermal (systemic)	5 mg/kg bw/day
110-82-7	cyclohexane	DNEL long-term oral (repeated)	59,4 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

110-82-7	cyclohexane	DNEL long-term dermal (systemic)	699 mg/kg
110-82-7	cyclohexane	DNEL long-term inhalative (systemic)	0,7 mg/L
141-78-6	ethyl acetate	DNEL acute inhalative (systemic)	0,734 mg/L
141-78-6	ethyl acetate	DNEL long-term inhalative (local)	0,734 mg/L
141-78-6	ethyl acetate	DNEL long-term dermal (systemic)	37 mg/kg
141-78-6	ethyl acetate	DNEL long-term inhalative (systemic)	0,037 mg/L
141-78-6	ethyl acetate	DNEL long-term oral (repeated)	4,5 mg/kg
141-78-6	ethyl acetate	DNEL acute inhalative (local)	0,367 mg/L
-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term dermal (systemic)	699 mg/kg
-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term inhalative (systemic)	608 mg/m³
-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term oral (repeated)	699 mg/kg
8050-09-7	rosin; colophony	DNEL long-term inhalative (systemic)	35 mg/m³
8050-09-7	rosin; colophony	DNEL long-term dermal (systemic)	10 mg/kg bw/day
8050-09-7	rosin; colophony	DNEL long-term oral (repeated)	10 mg/kg bw/day

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC soil, freshwater	1,04 mg/kg dw
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC sewage treatment plant (STP)	100 mg/L
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC sediment, freshwater	1,29 mg/kg dw
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC Secondary Poisoning	16,7 mg/kg
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC aquatic, marine water	0,4 µg/L
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC aquatic, freshwater	4 µg/L
128-37-0	2,6-di-tert-butyl-p-cresol	PNEC aquatic, intermittent release	4 µg/L
141-78-6	ethyl acetate	PNEC aquatic, freshwater	0,26 mg/L
141-78-6	ethyl acetate	PNEC aquatic, marine water	0,026 mg/L
141-78-6	ethyl acetate	PNEC sediment, freshwater	0,34 mg/kg
141-78-6	ethyl acetate	PNEC sediment, marine water	0,034 mg/kg
141-78-6	ethyl acetate	PNEC soil, freshwater	0,22 mg/kg
8050-09-7	rosin; colophony	PNEC aquatic, freshwater	0,002 mg/L
8050-09-7	rosin; colophony	PNEC aquatic, marine water	0 mg/L
8050-09-7	rosin; colophony	PNEC sewage treatment plant (STP)	1.000 mg/L
8050-09-7	rosin; colophony	PNEC sediment, freshwater	0,007 mg/kg dw
8050-09-7	rosin; colophony	PNEC sediment, marine water	0,001 mg/kg dw
8050-09-7	rosin; colophony	PNEC soil, freshwater	0 mg/kg dw

8.2 Exposure controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

Personal protection equipment

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device Use the following filter types for cleaning waste gases:

Hand protection

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material: $\geq 0,4$ mm
Breakthrough time: ≥ 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	light yellow
Odour	characteristic
pH at 20 °C	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	65 °C
Flash point	-18 °C
flammability	not applicable
Lower explosion limit at 20°C	1 Vol-%
Upper explosion limit at 20°C	11,5 Vol-%
Vapour pressure at 20°C	175 mbar
Relative vapour density	not applicable
Density at 20 °C	0,824 kg/L
Water solubility at 20°C	not determined
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	200 °C
Decomposition temperature	not determined
Dynamic viscosity at 20 °C	1.260

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Gases / vapours, highly flammable. Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Decomposition temperature not determined

10.5 Incompatible materials

Acid, concentrated, Oxidising agent, strong.

10.6 Hazardous decomposition products

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

2,6-di-tert-butyl-p-cresol

LD50: oral (Rat): > 5.000 mg/kg; (OECD 401)

LD50: dermal (Rat): > 5.000 mg/kg; (OECD 402)

cyclohexane

LD50: (Rat): > 5.000 mg/kg

LC50: inhalative (Rat): > 32,88 mg/L (4 h); (OECD 403)

LD50: dermal (Rabbit): > 2.000 mg/kg; (OECD 402)

ethyl acetate

LD50: oral (Rat): > 5.620 mg/kg

LD50: dermal (Rabbit): > 18.000 mg/kg

LC50: inhalative (Rat): = 56 mg/L (4 h)

hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

LD50: (Rat): > 5.000 mg/kg; (OECD 401)

LC50: (Rat): > 20 mg/L (4 h); (OECD 403)

LD50: dermal (Rabbit): > 2.000 mg/kg; (OECD 402)

* **rosin; colophony**

LD50: (Rat): > 2.000 mg/kg bw

* **LD50: dermal (Rabbit): > 2.000 mg/kg bw**

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

* **Overall assessment on CMR properties**

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

* **Endocrine disrupting properties**

* **This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.**

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Acute (short-term) fish toxicity

2,6-di-tert-butyl-p-cresol

LC0: (Danio rerio (zebrafish)): > 0,57 mg/L (96 h)

cyclohexane

LC50: (Pimephales promelas (fathead minnow)): = 4,53 mg/L (96 h)

ethyl acetate

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 230 mg/L (96 h)

hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 11,4 mg/L (96 h)

rosin; colophony

LC50: (Pimephales promelas (fathead minnow)): = 1,7 mg/L (96 h)

Method: OECD 203

Acute (short-term) toxicity to algae and cyanobacteria

2,6-di-tert-butyl-p-cresol

IC50: (Scenedesmus subspicatus): > 0,4 mg/L (72 h)

cyclohexane

ErC50: (Desmodesmus subspicatus): > 4,425 mg/L (96 h)

ethyl acetate

LC50: (Desmodesmus subspicatus): = 5.600 mg/L (48 h)

hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

EL50: (Pseudokirchneriella subcapitata): = 30 < x > 100 mg/L (72 h)

rosin; colophony

ErC50: (Pseudokirchneriella subcapitata): = 39,6 mg/L (72 h)

Method: OECD 201

Acute (short-term) toxicity to crustacea

2,6-di-tert-butyl-p-cresol

EC50 (Daphnia magna (Big water flea)): = 0,61 mg/L (48 h)

cyclohexane

EC50 (Daphnia magna (Big water flea)): = 0,9 mg/L (48 h)

ethyl acetate

EC50 (Daphnia magna (Big water flea)): = 165 mg/L (48 h)

hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

EL50: (Daphnia magna (Big water flea)): = 3 mg/L (48 h)

rosin; colophony

EC50 (Daphnia magna (Big water flea)): = 1,6 mg/L (48 h)

Method: OECD 202

12.2 Persistence and degradability

cyclohexane

Biodegradation; (Activated sludge) = 77 % (28 d)

Method: OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D

Readily biodegradable (according to OECD criteria).

hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Biodegradation; (Activated sludge) = 81 % (28 d)

Method: OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D

Readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

cyclohexane

Bioconcentration factor (BCF), (Pimephales promelas (fathead minnow)) = 167

Method: calculated

No indication of bioaccumulation potential.

Partition coefficient: n-octanol/water = 0,68

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

12.6* Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

*** Product/Packaging disposal**

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number

1133

14.2 UN proper shipping name

Land transport (ADR/RID)

Adhesives (ethyl acetate, cyclohexane)

Inland waterway craft (ADN)

Adhesives (ethyl acetate, cyclohexane)

Sea transport (IMDG)

Adhesives (contain ethyl acetate, cyclohexane)

Air transport (ICAO-TI / IATA-DGR)

Adhesives (contain ethyl acetate, cyclohexane)

14.3 Transport hazard class(es)

Land transport (ADR/RID)	3
Inland waterway craft (ADN)	3
Sea transport (IMDG)	3
Air transport (ICAO-TI / IATA-DGR)	3

14.4 Packing group

Land transport (ADR/RID)	II for packages < = 450 litres: III
Inland waterway craft (ADN)	II
Sea transport (IMDG)	II for packages < = 450 litres: III
Air transport (ICAO-TI / IATA-DGR)	II for packages < 30 litres: III

14.5 Environmental hazards

Land transport (ADR/RID)	ENVIRONMENTALLY HAZARDOUS
Sea transport (IMDG)	Marine pollutant / cyclohexane

14.6 Special precautions for user

Transport always in closed, upright and safe containers Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling see parts 6 - 8

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Classification code: F1
Limited quantity (LQ): 5 Liter
Tunnel restriction code: D/E
for packages < = 450 litres: E
Transport category: 2
Hazard identification number (Kemler No.): 33

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Inland waterway craft (ADN)

Classification code: F1
Limited quantity (LQ): 5 Liter

Sea transport (IMDG)

Limited quantity (LQ): 5 Liter
EmS-No.: F-E, S-D

Air transport (ICAO-TI / IATA-DGR)

Limited quantity (LQ): 1 Liter
Packing instruction: Y341
per package - passenger: 5 Liter
Packing instruction - passenger: 353
per package - cargo: 60 Liter
Packing instruction - cargo: 364

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

- * Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

- * VOC value: 653 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200t; Quantity 2: 500t

P5c FLAMMABLE LIQUIDS

Quantity 1: 5.000t; Quantity 2: 50.000t

National regulations

- * Observe in addition any national regulations!

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

	REACH No.	Substance name	CAS No. EC No.
*	01-2119555270-46	2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4
*	01-2119463273-41-0000	cyclohexane	110-82-7 203-806-2
*	01-2119475103-46	ethyl acetate	141-78-6 205-500-4
*	01-2119475514-35	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	- 921-024-6
*	01-2119480418-32	rosin; colophony	8050-09-7 232-475-7

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
* EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

140
Version 9.0

Vulkofest 96 toluene-free contact adhesive
Revision date 31-Aug-2023

Print date 31-Aug-2023

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	On basis of test data.
Eye Irrit. 2	Calculation method.
STOT SE 3 Narcotic effects	Calculation method.
Skin Irrit. 2	Calculation method.
Aquatic Chronic 2	Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.